



Cable ID: PCF6-10CC-0150-G

Date / Time: 06/10/2019 12:31:54 PM

Headroom 4.8 dB (NEXT 12-36)

Test Limit: TIA Cat 6 Channel

Cable Type: Cat 6 F/UTP

NVP: 70.0%

Software Version: V6.1 Build 3

Limits Version: V7.1

Calibration Start Date:

Main (Module): 12/03/2018

Remote (Module): 12/03/2018

Test Summary: PASS

Model: DSX-8000


Main S/N: 1820302

Remote S/N: 1824298


Main Adapter: DSX-CHA804

Remote Adapter: DSX-CHA804

Length (ft), Limit 328	[Pair 45]	199
Prop. Delay (ns), Limit 555	[Pair 36]	295
Delay Skew (ns), Limit 50	[Pair 36]	6
Resistance (ohms)	[Pair 36]	10.92
Insertion Loss Margin (dB)	[Pair 36]	16.4
Frequency (MHz)	[Pair 36]	250.0
Limit (dB)	[Pair 36]	35.9





Wire Map (T568B)





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-36	12-36	12-45	12-36
NEXT (dB)	11.0	4.8	27.1	5.6
Freq. (MHz)	3.4	153.5	229.0	179.5
Limit (dB)	64.2	36.8	33.8	35.6
Worst Pair	36	36	12	36
PS NEXT (dB)	10.4	4.3	28.7	5.3
Freq. (MHz)	3.4	157.5	229.0	184.0
Limit (dB)	61.7	33.7	30.8	32.5





PASS	MAIN	SR	MAIN	SR
Worst Pair	45-36	45-36	12-36	12-36
ACR-F (dB)	23.3	23.6	24.5	24.4
Freq. (MHz)	124.5	90.0	247.0	250.0
Limit (dB)	21.4	24.2	15.4	15.3
Worst Pair	36	45	36	36
PS ACR-F (dB)	24.1	24.0	24.1	24.5
Freq. (MHz)	247.5	67.8	247.5	250.0
Limit (dB)	12.4	23.6	12.4	12.3



N/A	MAIN	SR	MAIN	SR
Worst Pair	12-36	36-45	12-45	36-78
ACR-N (dB)	12.4	9.7	43.1	26.0
Freq. (MHz)	3.4	3.3	229.0	249.0
Limit (dB)	60.5	60.9	-0.4	-2.7
Worst Pair	36	36	12	36
PS ACR-N (dB)	11.8	8.7	44.4	24.5
Freq. (MHz)	3.4	3.3	229.0	250.0
Limit (dB)	58.0	58.4	-3.3	-5.8



PASS	MAIN	SR	MAIN	SR
Worst Pair	45	45	78	45
RL (dB)	10.4	7.0	18.7	10.9
Freq. (MHz)	16.9	7.9	246.5	135.5
Limit (dB)	17.9	19.0	8.1	10.7



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	5GBASE-T
ATM-25	ATM-51	ATM-155
100VG-AnyLan	TR-4	TR-16 Active
TR-16 Passive		