


WAF1-5203-06-00B

19" 6/3U WALL-MOUNTED CABINET



PRODUCT FEATURES:

- Two mounting rails: vertical 6U and horizontal 3U,
- A back panel with a mesh panel to which components can be attached with an M6 screw,
- Cable holes in the top and bottom panels that can be unscrewed,
- Knockout holes in the rear of the cabinet,
- Doors with the ability to open both ways,
- Ventilation holes located in the top, bottom panel and on the side walls.

PRODUCT SPECIFICATION:

Type of cabinet	Wall mount
Size	19",
ICT height	6 U
Assembly type	Assembled
Working depth	143 mm
Front door type	Metal
Door type	Single-leaf
Maximum front door opening angle	220 °
Maximum static load	60 kg
Number of vertical rails	2
Thermostat	No
LCD panel	No
Colour	Black
RAL color	RAL9004
Weatherproof rating	IP20
Front door thickness	1 mm
Mounting rails thickness	1,5 mm
Frame thickness	1,2 mm
Other elements sheet thickness	1 mm
Depth	200 mm
Width	540 mm
Height	540 mm
Weight	11 kg
Standard	ANSI/EIA RS-310-D, DIN 41491/PART 1, DIN 41494/PART 7, ETSI, IEC297-2:1982
Grounding Details	Front door, Bottom panel
Included Accessories	User Manual, Grounding cable, DIN rail TS-35, M6 screws, Front lock