

RSFE-16P-2C-250

**250W POE+
16X100MB/S
UPLINK 1GB/S**



PRODUCT FEATURES:

- 250W POE+ unmanaged 16x100Mb/s Combo Uplink
- metal housing, Standard,VLAN,Extend modes
- set allows installation in 19" rack cabinets

PRODUCT SPECIFICATION:

Number of Ethernet ports	18
Number of fiber ports	2
Number of POE ports	16
Ports specification	2x RJ45 port (1 Gbps) or 2x SFP slot (1 Gbps) - Combo UpLink , 16x 100BASE-T 802.3af / 802.3at PoE+
Maximum network link speed	1 Gbps
Network Link Type	Ethernet, Fiber
Size	19",
PoE support	Yes
PoE standards	802.3at, 802.3af
PoE power supply type	PoE, PoE+
Total budget for PoE	250 W
Maximum power per port	30 W
Bandwidth	7,2 Gbps
MAC address table	16K
Cooling	Active - fan
Power Requirements	100-240V AC
Power consumption	250 W
Surge protection	6 kV
Work signal	LED
Wired standards	IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3x (Flow-Control), IEEE 802.3af PoE, IEEE 802.3at PoE+
Functions	Intelligent PoE port disconnection function, Extend mode, VLAN
ICT height	1 U
Dimensions	208 x 320 x 45 mm
Weight	1,9 kg
Environment temperature	from 5 up to 55 °C
Environment humidity	from 0 up to 80 %